

Wireless Hygro-Thermometer System

Monitors local plus up to six remote locations from one base station

Features:

- Base station's large LCD displays local Time, Indoor Temperature and % Relative Humidity plus measurements for up to 6 locations using remote transmitters
- Measures Relative Humidity from 20 to 90% and Temperature from 32 to 104°F or 0 to 40°C (receiver) and 14 to 122°F or -10 to 50°C (transmitter)
- Resolution: 1% RH, 0.1°F or 0.1°C
- Internal clock with Alarm
- Transmitter can be wall mounted up to 90 feet from the receiver
- Remote transmitter's LCD displays time, temperature and % RH
- Transmitter sends updated signal every 6 minutes; base station updates every 1 minute
- Operates at 433MHz; FCC approved
- Ideal for monitoring remote office areas, clean rooms, green houses, storage facilities and refrigeration units
- System complete with one base station (includes fold-up stand, 3 AA batteries and AC adaptor) and one transmitter (includes 2 AAA batteries)



Wireless Hygro-Thermometer Station



Remote Transmitters #1.....#6

Specifications	Range	Resolution	Basic Accuracy
Humidity:	20 to 90%	1%	±5%
Temperature:			
Receiver:	32 to 104°F (0 to 40°C)	0.1°F/°C	±1.8°F/±1.0°C
Transmitter:	14 to 122°F (-10 to 50°C)		
Dimensions:	Base: 4.5 x 5.9 x 1.2" (115 x 150 x 30mm)		
	Transmitter: 4.2 x 2.4 x 1.1" (106 x 60 x 28mm)		
Weight:	Base: 7.4oz (210g)		
	Transmitter: 3.2oz (90g)		

Ordering Information:

TH433Wireless Hygro-Thermometer System, 117VAC
 TH433-2Wireless Hygro-Thermometer System, 230VAC
 TH437Replacement RH/Temperature Transmitter
 409997Vinyl Pouch Carrying Case