



General Purpose Gauges

Series P-570K Low Cost Utility Gauges for the OEM

DESCRIPTION

connections.

U.S. Gauge P-570K utility gauges provide economical, reliable service in a wide range of applications including pumps, compressors, and other equipment. Series P-570K utility gauges come in ranges of: 0 to 30, 60, 100, 160, 200, and 300 psi, with accuracy of ±3-2-3% of span. Gauges are available in 2" polypropylene cases with 1/8-27 or 1/4-18 NPT center-back or lower mount



SPECIFICATIONS

RANGE: 0-30, 60, 100, 160, 200, 300 psi (dual scale or

metric available)

ACCURACY: ±3-2-3% of span (Grade B) BOURDON TUBE: Phosphor bronze

WINDOW: Polycarbonate

DIAL: ABS (aluminum optional)


POINTER: Aluminum


CASE: Polypropylene

CONNECTION: 1/8-27 NPT, 1/4-18 NPT, center-back or lower

mount







NOTES:

THREAD 1/8-27 NPT (A1, B1) OR 1/4-18 NPT (A2, B2)
TOLERANCES 2 PLACE DEC. ±0.02, 3 PLACE DEC. ±0.010

© 2006, by AMETEK, Inc. All rights reserved. PDF606 (160126) Specifications are subject to change without notice. Visit our Web sites for the most up-to-date information.





U.S. GÁUGE 820 Pennsylvania Blvd. Feasterville, PA 19053 U.S.A. Tel: (215) 355-6900 Fax: (215) 354-1802 www.ametekusg.com Customer Service Tel: (863) 534-1504 Customer Service Fax: (863) 533-7465

For Gauges/Thermometers:

For Electronic Products:
PMT PRODUCTS
820 Pennsylvania Blvd.
Feasterville, PA 19053 U.S.A.
Tel: (215) 355-6900
Fax: (215) 354-1800
www.ametekusg.com

For Diaphragm Seals: M&G PRODUCTS 8600 Somerset Drive Largo, FL 33773 U.S.A. Tel: (727) 536-7831 Fax: (727) 539-6882 www.ametek.com/tci