

Temperature Products

New!

MADE IN USA

Model BACO 2" Back Connected Industrial Bimetallic Thermometers

DESCRIPTION

U.S. Gauge offers 2"
heavy duty, industrial
bimetallic thermometers
with a standard rear 1/4-18 NPT
connection. These thermometers,
with 304 stainless steel
construction, are rugged and
commonly used in light industrial
and OEM applications. The
thermometers may be silicone filled
for additional vibration dampening.

A variety of lens materials are available including acrylic, polycarbonate, and tempered glass. Standard stem diameter, up to 42" long, is .25". Other available stem sizes are .24" (6 mm), and .375" (9.52 mm).



SPECIFICATIONS

STEM DIAMETER: .25" standard up to 42" stem

CONNECTION: 1/4-18 NPT

EXTERNAL RESET: Easy to calibrate by loosening the socket head screw (above hex connecting nut) with 5/64" hex wrench

CONSTRUCTION: 304 stainless steel external parts, welded construction; corrosion resistant to most chemicals

HERMETIC SEAL: Per ASME B40.3, dustproof and leakproof


DIAL: Anodized aluminum with large black numbers and graduations

LENS: Glass

BIMETALLIC COIL: Helix coil is silicone coated on ranges below 500°F for vibration dampening and to maximize heat transfer and response time

ACCURACY: ±1% full span per ASME B40.3 Grade A

OVER TEMPERATURE LIMITS: Up to 250°F, 100%; 250° to 550°F, 50%; 550° to 1000°F, continuous use up to 800°F, intermittent use over 800°F



SPEC NUMBER SELECTION CHART

Model BACO-2			2" Dial Size			
Connection	Temperature Range*	2-1/2" Stem Length Spec No.	4" Stem Length Spec No.	6" Stem Length Spec No.	9" Stem Length Spec No.	12" Stem Length Spec No.
50 to 550 FC	415152	415154	415156	415158	415160	

^{*} All dials are dual scale, Fahrenheit outer scale, Celsius inner scale

© 2006, by AMETEK, Inc. All rights reserved. PDF606 (160126) Specifications are subject to change without notice. Visit our Web sites for the most up-to-date information.



For Gauges/Thermometers:
U.S. GAUGE
820 Pennsylvania Blvd.
Feasterville, PA 19053 U.S.A.
Tel: (215) 355-6900
Fax: (215) 354-1802
www.ametekusg.com
• Customer Service Tel: (863) 534-1504

Customer Service Fax: (863) 533-7465

For Electronic Products:
PMT PRODUCTS
820 Pennsylvania Blvd.
Feasterville, PA 19053 U.S.A.
Tel: (215) 355-6900
Fax: (215) 354-1800
www.ametekuso.com

For Diaphragm Seals: M&G PRODUCTS 8600 Somerset Drive Largo, FL 33773 U.S.A. Tel: (727) 536-6882 www.ametek.com/fci

