## RAYNGER® MINITEMP™ MT SERIES

## NON CONTACT THERMOMETERS: FITS IN A POCKET. PRICED FOR ANY TOOLBOX.

Raytek's MiniTemp Non-Contact Thermometer is small enough to fit in a pocket and comes in two models: MiniTemp MT2 without laser sighting, or MiniTemp MT4 with laser sighting.

Either model has a temperature range from -18 to 260°C and a response rate of 500 mSec for each measurement reading. The distance to spot ratio is 6:1.

The light-weight Mini Temp Non-Contact Thermometer is perfect for facility maintenance (both preventative and predictive), machinery inspection, equipment audits, electrical troubleshooting and a range of additional applications and uses.



• RAYMT2

Emissivity preset at 0.95; 0 to 500°F (-18 to 260°C)

RAYMT4

Emissivity preset at 0.95; 0 to 500°F (-18 to 260°C) FDA & IEC Class II laser warning label in English

## **SPECIFICATIONS**

TEMPERATURE RANGE	0 to 500°F (-18 to 260°C)
ACCURACY AT 73°F (23°C)	±2% or ±3.5°F (±2°C), whichever is greater; For targets at 0 to 30°F (-18 to -1°C), ±5°F (±3°C)
REPEATABILITY AT 73°F (23°C)	±2% of reading or ±3°F (±2°C), whichever is greater
RESPONSE TIME	(95%) 500 mSec
AMBIENT OPERATING RANGE	32 to 122°F (0 to 50°C)
EMISSIVITY	Preset to .95
LASER (MT4 ONLY)	Class II
DISPLAY	7 second hold, LCD backlight, °F or °C selectable
DISTANCE TO SPOT RATIO	6:1
POWER	9V Alkaline or NiCd battery
WEIGHT	0.5 lb (227g)
DIMENSIONS	6 x 4 x 1.5 in (152 x 101 x 38 mm)

## RAYNGER ST ORDERING INFORMATION

RAYMT2	Hand-held non-contact infrared thermometer	\$ 79.00
RAYMT4	Hand-held non-contact infrared thermometer with Class II laser	99.00
ACCESSORIES		
RAYMTAPK	Accessory kit with wrist strap and pouch	\$ 9.95