

PROTECTION TUBES AND HEADS

This Section Contains



Metal Protection Tubes 



Thermocouple Heads 



Protection Tube Reference Data 

Please CALL For Quote!

If you can't find what you need call!


From Illinois 618-465-7623

From St. Louis 314-231-0752

Fax 618-465-7679

E-mail info@ipscustom.com

METAL PROTECTION TUBES



MPT - - - - - - - _____ "S" for Special
 "0" for No

Fraction

A = 1/8"

B = 1/4"

C = 3/8"

D = 1/2"

E = 5/8"

F = 3/4"

G = 7/8"

0 = None

F R A C T I O N

F R A C T I O N

VC for vented coupling
00 if none

Immersion length in inches
00 to 99 (00 if no bushing)

Bushing (00 if no bushing)

Length in inches
00.0 to 99.0

Alloy and size-Style

ALLOY & SIZE

Material		Size		Schedule	
Carbon Steel	C	1/2"	2	40	4
304 Stainless	4	3/4"	3	80.	8
310 Stainless	0	1"	4		
316 Stainless	6	1 1/2"	6	.	
Inconel 600	I				
446 Stainless	H				
Other	X				

BUSHING CHART

Male Pipe Thread	Carbon Steel	Stainless Steel
3/4"	B3	S3
1"	B4	S4
1 1/4"	B5	S5
1 1/2"	B6	S6
2"	B8	S8

Note: Other alloys and sizes available upon request.
 Ex: 310 SS, 3/4", Schedule 40 = 034

INDUSTRIAL PROCESS AND SENSOR


ALTON, ILLINOIS, USA

TEL. 618-465-7623


FAX. 618-465-7679

www.ipscustom.com

INDUSTRIAL THERMOCOUPLE ASSEMBLY



Thermocouple Assembly w/ Metal Protection Tube



Thermocouple Assembly w/ Ceramic Protection Tube

If thermocouple is required then order the **Thermocouple Element**, by part number and mark "Assembly" with an "A".

If **Dual Tube** (ceramic and metal) is required then order Ceramic assembly, mark "Dual Tube" box with a "D" and order the Metal Protection Tube separately.

Note: If this is getting confusing, then call the factory for the part number.

Fraction		
A = 1/8"	D = 1/2"	G = 7/8"
B = 1/4"	E = 5/8"	0 = None
C = 3/8"	F = 3/4"	

PREFIX	TA
TUBE STYLE Select style from Page 2 for Metal Protection Tube or Page 3 for Ceramic Protection Tube.	
LENGTH In Inches	
FRACTION	
ASSEMBLY Use "A" if thermocouple to be included, "0" if none.	
DUAL TUBE If dual tube required "D" or "0" for none.	
HEAD Select Head from Chart on Page 6 .	
BUSHING Select bushing from table on Page 2 , "FL" for Flange or "00" if none.	
IMMERSION LENGTH In Inches	
FRACTION	
"S" for Special "0" for No	

INDUSTRIAL PROCESS AND SENSOR

ALTON, ILLINOIS, USA

TEL. 618-465-7623

FAX. 618-465-7679

www.ipscustom.com

THERMOCOUPLE HEAD P/N for Assemblies

Use Table 6 to choose the head number and Table 6A to choose the size of the head for a Protection Tube assembly.

Table 6

Head No.	Head Description	Part No.	Terminal Block Description
A	IPS Cast Aluminum Head. Stainless Steel cover. Thumb screw for easy cover removal.	HTB-7A	Single element with lift out bail
B	Standard Cast Aluminum Head with screw cover	HTB-M-100 HTB-M-108 HTB-M-200 HTB-M-300	Single element block Single element 8 AWG Dual Element 6-way terminal block
C	Standard Cast Iron Head with screw cover		
D	Cast Aluminum Head with hinged snap lever cap	HTB-TC-E-2PC HTB-TC-N2PC HTB-TC-N4PC HTB-TC-N6PC	2 pole elliptical Round single element 8 AWG Round dual Element Round 6-way
E	Large Cast Iron Head	HTB-M-100 HTB-M-108 HTB-M-200 HTB-M-300	Single element block Single element 8 AWG Dual Element 6-way terminal block
F	Mini Aluminum Head for MgO ONLY	Built in	As required Single or Dual
G	Explosion Proof Head	HTB-M-100 HTB-M-108 HTB-M-200 HTB-M-300	Single element block Single element 8 AWG Dual Element 6-way terminal block

Table 6A





Head Sizes			
Head Size	Process x Conduit	Head Size	Process x Conduit
1	1/2" x 1/2"	4	1/2" x 3/4"
2	3/4" x 1/2"	5	3/4" x 3/4"
3	1" x 1/2"	6	1" x 3/4"

When selecting a head for an assembly, the first digit will be the **Head No.** and the second digit is the **Head Size**. For example **C5** is a cast iron head with a 3/4" NPT process connection and a 3/4" NPT conduit connection.

INDUSTRIAL PROCESS AND SENSOR	ALTON, ILLINOIS, USA
TEL. 618-465-7623	FAX. 618-465-7679
	www.ipscustom.com

THERMOCOUPLE HEADS

Table 8

Head No.	Head Description	Part No.	Available Terminal Block Description
H-7-X¹	IPS cast aluminum Head. Stainless Steel cover. Thumb screw for easy cover removal.		♦ Single element with lift out bail
H-7-A-X¹	Standard cast aluminum head with screw cover		♦ Single element block ♦ Single element 8 AWG
H-7-CI-X¹	Standard cast iron head with screw cover		♦ Dual Element ♦ 6-way terminal block
H-KNPL-X¹	Cast Aluminum Head with hinged snap lever cap		♦ 2 pole elliptical ♦ Round single element 8 AWG ♦ Round dual Element ♦ Round 6-way
H-LCI-X¹	Large Cast Iron Head		♦ Single element block ♦ Single element 8 AWG ♦ Dual Element ♦ 6-way terminal block
H-SMAH	.250 MgO Head Mini Aluminum Head Single Termination		♦ Single Termination
H-DMAH	.250 MgO Head Mini Aluminum Head Dual Termination		♦ Dual termination
H-EX-X¹	Explosion Proof Head		♦ Single element block ♦ Single element 8 AWG ♦ Dual Element ♦ 6-way terminal block

¹ **Note:** The last X in the Head P/N designates the Process x Conduit sizes. See Table 8A, next page.

INDUSTRIAL PROCESS AND SENSOR

ALTON, ILLINOIS, USA

TEL. 618-465-7623

FAX. 618-465-7679

www.ipscustom.com

Thermocouple Head Size Selection

Use table 8A to select the head size for the thermocouple heads in Table 8.

Example: If you want an IPS Thermocouple head with, a cast aluminum body and a stainless steel cover, select an H-7 head.

And you want 1/2" X 1/2" connections, select Head Size 1 from Table 8A. Use the 1 to replace the "X" in the head P/N above.

The full part number of the thermocouple head is H-7-1

TABLE 8A

Head Sizes			
Head Size	Process x Conduit	Head Size	Process x Conduit
1	1/2" x 1/2"	4	1/2" x 3/4"
2	3/4" x 1/2"	5	3/4" x 3/4"
3	1" x 1/2"	6	1" x 3/4"

Terminal Block Part Numbers

Table 8B

Head No.	Head Description	Terminal Block Part No.	Terminal Block Description
H-7	IPS Cast Aluminum Head. Stainless Steel cover. Thumb screw for easy cover removal.	HTB-7A	◆ Single element with lift out bail
H-7A	Standard Cast Aluminum Head with screw cover	HTB-M-100 HTB-M-108 HTB-M-200 HTB-M-300	◆ Single element block ◆ Single element 8 AWG ◆ Dual Element ◆ 6-way terminal block
H-CI	Standard Cast Iron Head with screw cover		
H-KNPL	Cast Aluminum Head with hinged snap lever cap	HTB-TC-E-2PC HTB-TC-N2PC HTB-TC-N4PC HTB-TC-N6PC	◆ 2 pole elliptical ◆ Round single element 8 AWG ◆ Round dual Element ◆ Round 6-way
H-LCI	Large Cast Iron Head	HTB-M-100 HTB-M-108 HTB-M-200 HTB-M-300	◆ Single element block ◆ Single element 8 AWG ◆ Dual Element ◆ 6-way terminal block
H-EX	Explosion Proof Head	HTB-M-100 HTB-M-108 HTB-M-200 HTB-M-300	◆ Single element block ◆ Single element 8 AWG ◆ Dual Element ◆ 6-way terminal block

INDUSTRIAL PROCESS AND SENSOR

ALTON, ILLINOIS, USA

TEL. 618-465-7623

FAX. 618-465-7679

www.ipscustom.com

PROTECTION TUBE DATA

MATERIAL	SIZE	OPERATING TEMP. °F	REMARKS
	Thread ID OD		
600 Inconel	1/2" .622 x .840 3/4" .824 x 1.050 1" 1.049 x 1.315	2220	Generally used for high temperature. Good corrosion resistance.
304 Stainless	1/2" .622 x .840 3/4" .824 x 1.050 1" 1.049 x 1.315	1800	Good corrosion resistance. Embrittles in the 900 – 1450 °F range.
310 Stainless	1/2" .622 x .840 3/4" .824 x 1.050 1" 1.049 x 1.315	2100	High mechanical and creep strength at elevated temperatures. Very good corrosion resistance.
316 Stainless	1/2" .622 x .840 3/4" .824 x 1.050 1" 1.049 x 1.315	1700	Higher corrosion resistance than 304. Resists pitting in sulfuric, phosphoric acids.
446 Stainless	1/2" .622 x .840 3/4" .824 x 1.050 1" 1.049 x 1.315	2000	Highly resistant to sulfur attack. General purpose alloy.
Carbon Steel	1/2" .622 x .840 3/4" .824 x 1.050 1" 1.049 x 1.315	1000	For non-corrosive gases and liquids. Scales quickly at higher temperatures.
Alumina	1/4" x 3/8" 7/16" x 11/16" 1/2" x 3/4" 1" x 1-1/8" 1" x 1-1/4"	Max. 3400 °F	Susceptible to thermal shock, needs preheating. Good mechanical strength. Resists chemicals and will not contaminate platinum.
Mullite	1/4" x 3/8" 7/16" x 11/16" 1/2" x 3/4" 1" x 1-1/8" 1" x 1-1/4"	Max. 2800 °F	Good resistance to thermal shock and chemicals. Good mechanical strength. Glazed tube recommended for generator and atmosphere furnaces. Can contaminate the platinum element above 2400 °F

Data available on other materials upon request.

INDUSTRIAL PROCESS AND SENSOR	ALTON, ILLINOIS, USA
TEL. 618-465-7623	FAX. 618-465-7679
	www.ipscustom.com