



Temperature Products

New!

MADE IN USA

Model POC 1" Testing and Spot Checking Thermometers

DESCRIPTION

U.S. Gauge offers a pocket sized thermometer used by inspectors, service and maintenance personnel, and technicians for general checking in food service, refrigeration, air conditioning, hot asphalt, and food processing applications.

These thermometers have a .15" standard stem diameter and a threaded connection that can be adapted for OEM applications with limited space considerations.



SPECIFICATIONS

STEM LENGTH: 5" (127 mm)

STEM DIAMETER: .15"

CONNECTION: Recal nut is standard

EXTERNAL RESET: Friction nut design for easy calibration

CONSTRUCTION: 304 stainless steel external parts, welded

construction; corrosion resistant to most chemicals

HERMETIC SEAL: Per ASME B40.3, dustproof and leakproof

DIAL: Anodized aluminum with large black numbers and

graduations

LENS: Polycarbonate lens is standard

BIMETALLIC COIL: Helix coil is silicone coated on ranges below 500°F for vibration dampening and to maximize heat transfer and response time

ACCURACY: ±1% full span per ASME B40.3 Grade A


OVER TEMPERATURE LIMITS: Up to 250°F, 100%; 250° to 550°F, 50%; 550° to 1000°F, continuous use up to 800°F, intermittent use over 800°F

POCKET SHEATH: Standard

STANDARD RANGES:

FAHRENHEIT	DEGREE DIVISION
*0° to 250°	2° increments
*50° to 500°	5° increments

 ^{*} Additional ranges are available – please consult factory at (863) 534-1504 NSF® approved for food service applications



SPEC NUMBER SELECTION CHART

Model POC-1		1" Dial Size
Connection	Temperature Range	5" Stem Length
		Spec No.
1/2-14 NPT	50 to 500°F	415000
	0 to 250°F	415001

© 2006, by AMETEK, Inc. All rights reserved. PDF606 (160126) Specifications are subject to change without notice. Visit our Web sites for the most up-to-date information





Customer Service Fax: (863) 533-7465

For Gauges/Thermometers: